

Mimo Vue with Bright Sign Built-In

Model: MBS-1080C/MBS-1080C-POE



A truly brilliant, smart, and professional tablet With BrightSign Hd3 Series Built-In Digital Signage Module

10.1" Wide Viewing Angle Digital Signage Platform

Two trusted powerhouse digital signage leaders—Mimo Monitors and BrightSign—have teamed up to bring you the brand new Mimo Vue with BrightSign Built-In. Bringing to market a fully encompassing, reliable, all-in-one digital signage solution, this new partnership leverages the power of the Mimo Vue technology and integrates the industry-leading BrightSign Platform. The result is a high quality, easy-to-install solution that's immediately digital signage ready, making it extremely simple to use, especially for those already reliant on the BrightSign platform.

The Mimo Vue HD is the second generation of Mimo Monitors 10.1" monitor line. It features a modern zero bezel design, a nearly 180 degree viewing angle from its bright, high contrast, IPS screen, and a resolution of 1280x800, that can display in either landscape or portrait orientations. Available with an optional base, the VESA75 pattern on the back is available where wall or pole mounting is desired.

BrightSign Built-In

The BrightSign Built-In Digital Signage Module is an HD Series 3 class BrightSign player. The BrightSign Built-In module is compatible with all BrightSign software, services and supported CMS solutions.

General Specifications

- 10.1" diagonal, IPS, 16:10, 1280x800 Resolution, Viewing angles: 85/85/85/85, Contrast ratio: 800:1
- 10 point capacitive touch panel
- Screen can be mounted with integrated VESA 75
- Lightweight, weighs less than 2 pounds
- BrightSign HD3 series module supports HTML5 and FHD (1080p60) video
- Gigabit Ethernet, USB 2.0, Audio out (analog and digital), GPIOx4 and storage on microSD
- Power over PoE+ Optional
- Mechanical drawings available upon request

Applications

- Kiosk information system
- Gaming and amusement
- POP/POS

BrightSign®
Built-In

Specifications

Item	Symbol	Min.	Typ.	Unit.
Contrast Ratio	CR	500	800	-
Average Luminance of White	LAVE	300	400	cd/m2
Viewing Angle	$\theta x+$, $\theta x-$, $\theta y+$, $\theta y-$	80	85	Deg.
Decoder		Single 1080p60 video decodings		
Media Formats		Video Codecs: H.265, H.264(MPEG-4, Part 10), MPEG-2, MPEG-1		
		Video Containers: .ts, .mpg, .vob, .mov, .mp4, .m2ts, .wmv		
		Images: BMP, JPEG, PNG		
		Audio: MP2, MP3, AAC, and WAV (AC3 is passed through)		
		HTML5 (Mainstream)		
HARDWARE INTERFACES				
External micro SD Slot (SDHC and SDXC);		SDHC storage up to 32GB		
		SDXC storage up to 2TB		
USB 2.0 High Speed Host Port		also supports content updates		
Phoenix GPIO Port		4-pin bi-directional terminal block		
RS-232 Serial Port				
Audio Out		analog & digital		
Ethernet		1000baseT plus optional PoE		
FEATURES		All standard BrightSign features of HD3 family		
SOFTWARE		Free BrightAuthor Software		
		BrightSign Networking Options		

Monitor Mounting Options



Shown with optional monitor mounts

Mimo Monitors
 743 Alexander Rd. Suite 15
 Princeton, NJ 08540

info@mimomonitors.com

Sales: **1-855-YES-MIMO (937-6466)**